

**AMENDMENTS TO THE CLAIMS**

Please replace claim 47, as shown below. All pending claims are reproduced below, including those that remain unchanged.

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims**

1. (Previously Presented) A system for placing and maintaining anchored conversations within an artifact comprising a file having a file type, the system comprising:

an application configured to access the artifact, wherein the application is associated with the file type;

a conversation client configured to access said anchored conversation and to receive communications regarding a portion of the artifact, while the artifact is viewed within the application;

an anchor configured to identify a location within said artifact with which said conversation client is associated; and

a conversation coordinator configured to maintain a relationship between the anchor, the conversation client and the anchored conversation.

2. (Previously Presented) The system according to claim 1, wherein said conversation coordinator and said conversation client are separate applications linked together by communications such that said conversation coordinator directs initiation and positioning of said conversation client.

3. (Previously Presented) The system according to claim 1, wherein the application is configured to allow access to sections of the artifact outside the anchor.

4. (Previously Presented) The system according to claim 1, further comprising:  
a database configured to store conversations received by said conversation client;  
wherein said conversation coordinator is further configured to allow a user access to any current or previous conversations stored in said database.

5. (Original) The system according to claim 1, wherein:  
said conversation coordinator comprises,  
a request handler configured to receive conversation requests from a requesting conversation client, and

a client mechanism configured to initiate a recipient conversation client having an anchor position, application, and artifact equivalent to the application, artifact, and anchor position of the requesting conversation client.

6. (Original) The system according to claim 5, wherein said request handler includes an approval mechanism that identifies whether an intended recipient of the conversation request approves entering into an anchored conversation.

7. (Original) The system according to claim 6, wherein said approval mechanism includes an id device that identifies all participants of a conversation to the intended recipient.

8. (Original) The system according to claim 5, wherein:  
said client mechanism comprises,  
a startup mechanism configured to initiate a target application associated with a conversation request received by the request handler;  
a retrieval mechanism configured to retrieve an artifact associated with the conversation request and load the retrieval artifact into the target application;  
a connection manager configured to establish a communications link with the requesting conversation client and the recipient conversation client; and  
an anchor device configured to locate and attach the recipient conversation client to the equivalent anchor position in the retrieved artifact.

9. (Original) The system according to claim 8, wherein said anchor device is further configured to track a location of said equivalent anchor position, and position a user interface of the conversation client to within a predetermined proximity of the anchor if a position of the anchor is moved.

10. (Original) The system according to claim 8, wherein said anchor device comprises:  
an attachment device configured to maintain a position of the conversation client relative to the corresponding anchor;

an unattach device configured to disassociate the position of the conversation client from a corresponding anchor; and

a reattachment device configured to re-attach a detached conversation client to the position of its corresponding anchor.

11. (Original) The system according to claim 8, further comprising:  
a database configured to store communications between conversation clients; and  
a conversation retrieval mechanism configured to retrieve previous communications from the database that are associated with the requesting conversation client and load the retrieved previous communications into at least the recipient conversation client.

12. (Original) The system according to claim 11, wherein:  
said connection manager establishes a connection that connects said database to the initiated conversation client so that said database is a silent participant that logs any conversations participated in by the initiated conversation client into said database.

13. (Original) The system according to claim 1, further comprising:  
a database mechanism configured to store conversation information of the conversation client in a database.

14. (Original) The system according to claim 13, wherein said conversation information includes a history of at least one of a location in the artifact of an anchor corresponding to the conversation client, and communications between the conversation client and another client.

15. (Original) The system according to claim 1, further comprising:  
an API mechanism configured to initiate at least one target application and load an artifact into the target application; and

an anchor device configured to anchor a conversation client to one of the artifact and an anchor of the artifact.

16. (Original) The system according to claim 15, wherein said API mechanism includes at least one application control device configured to direct operations of at least one target application via a target application programming interface.

17. (Original) The system according to claim 5, wherein said conversation coordinator further comprises a synchronization device configured to notify a user of the recipient conversation client if the artifact associated with the recipient conversation client becomes out of sync with a master document.

18. (Original) The system according to claim 17, wherein said synchronization device includes an activatable input mechanism by which a user may activate a synchronization process to update the out of synch artifact.

19. (Original) The system according to claim 17, wherein said conversation coordinator further comprises an update mechanism configured to update the artifact based on changes to the master document.

20. (Original) The system according to claim 17, wherein said master document is the artifact of the requesting conversation client.

21. (Original) The system according to claim 5, wherein said conversation coordinator further comprises an anchor identification mechanism configured to identify other anchored conversations in the artifact of the recipient conversation client and one of highlight, grey, and make invisible each identified anchor based on a predetermined access/privacy setting.

22. (Original) The system according to claim 1, wherein said conversation coordinator comprises:

Attorney Docket: FXPL-01000US0  
U.S. Application No. 09/391,069  
ssvoboda/fxp/1000us0/Reply D as filed.doc

a client mechanism configured to initiate a conversation client; and  
an anchor device configured to position the conversation client relative to one of said application and an anchor of said artifact.

23. (Original) The system according to claim 1, wherein said conversation coordinator further comprises a messaging device configured to receive messages from said application.

24. (Original) The system according to claim 23, wherein said messages include at least one of an anchor position, invocation of an anchored conversation, and adding an anchor.

25. (Original) The system according to claim 1, wherein said conversation coordinator includes a communications device configured to route communications, from the conversation client to a communications network, and from the communications network to the conversation client.

26. (Original) The system according to claim 25, wherein said communications device is an IRC client configured to pass and retrieve communication to an IRC network.

27. (Original) The system according to claim 1, wherein:  
said conversation coordinator includes a database mechanism configured to connect a remote database as a silent participant to the conversation client.

28-32 (Canceled)

33. (Previously Presented) A system for invoking anchored conversations having artifacts of applications as a context, comprising:

an application conversation interface (ACI) having an application access mechanism that allows access and manipulation of application operations of each of the said applications;

an anchor mechanism configured to identify and attach a conversation client to a selected anchor position in an artifact; and

a communications device configured to route communications, from the conversation client to a communications network, and from the communications network to the conversation client;

wherein said communications device is an IRC client configured to pass and retrieve communication to an IRC network.

34. (Original) The system according to claim 33, wherein said conversation client comprises a communication client capable of any one of text, sound, graphic, tactile, video, and other communication mediums.

35. (Original) The system according to claim 33, further comprising:  
a conversation coordinator configured to,  
receive initiation requests from an application,  
initiate a conversation client to be anchored at an anchor position associated with the initiation request, and

send anchored conversation request for initiating an anchored conversation client at a recipient host having a same application, artifact, and anchor position as the requesting conversation client.

36-46 (Canceled)

47. (Currently Amended) A system for anchored conversations, comprising:  
means for initiating and maintaining conversation clients at each of a requesting host and a recipient host, including,

means for receiving an anchored conversation request from an application at a requestor host, said application having an artifact with an anchor identifying a location of an anchored conversation;

means for initiating a requestor conversation client associated with the application at a requestor host;

means for anchoring said requestor conversation client, comprising a means for maintaining a position of said requestor conversation client relative to said anchor of said artifact of said application at said requestor host;

means for requesting startup of a recipient conversation client;  
means for starting said application at a recipient host;  
means for retrieving a copy of said artifact into said application at said recipient host; and  
means for anchoring said recipient conversation client, comprising a means for maintaining a position of said recipient conversation client relative to said anchor of said artifact of said application at said recipient host;

wherein said means for anchoring further comprise:

request means configured to receive conversation requests from a requesting conversation client; and

a client mechanism means configured to initiate a recipient conversation client having an anchor position, application, and artifact equivalent to the application, artifact, and anchor position of the requesting conversation client; and

an anchor identification means configured to identify other anchored conversations in the artifact of the recipient conversation client and to one of highlight, grey, and make invisible each identified anchor based on a predetermined access/privacy setting.

48. (Previously Presented) A system for placing and maintaining anchored conversations within an artifact comprising a file having a file type, the system comprising:

an application configured to access the artifact, wherein the application is associated with the file type;

a conversation client configured to access said anchored conversation and to receive communications regarding a portion of the artifact, while the artifact is viewed within the application, wherein the communications are received from a party having access to the file;

an anchor configured to identify a location within said artifact with which said conversation client is associated; and

a conversation coordinator configured to maintain a relationship between the anchor, the conversation client and the anchored conversation.